

SIMATIC S7-300, ANALOG INPUT SM 331, GALVANICALLY ISOLATED, 8 AI, 14 BIT, 0.052 MS/CHANNEL, CURRENT, VOLTAGE, INTERRUPTS, DIAGNOSTICS, 1 X 20 PIN, FIT FOR ISOCHRON MODE IMPROVED DP-CYCLE TIME FOR ISOCHRON MODE



Figure similar

### Supply voltage

#### Load voltage L+

- Rated value (DC) 24 V
- Reverse polarity protection Yes

### Input current

from load voltage L+ (without load), max.	50 mA
from backplane bus 5 V DC, max.	100 mA

### Power loss

Power loss, typ.	1.5 W
------------------	-------

### Analog inputs

Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	20 V; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20)
permissible input current for current input (destruction limit), max.	40 mA

### Input ranges

- Voltage Yes
- Current Yes

• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
<b>Input ranges (rated values), voltages</b>	
• 0 to +10 V	No
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	100 kΩ
• -1 V to +1 V	Yes
• Input resistance (-1 V to +1 V)	10 MΩ
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	100 kΩ
• -5 V to +5 V	Yes
• Input resistance (-5 V to +5 V)	100 kΩ
• -500 mV to +500 mV	Yes
• -80 mV to +80 mV	Yes
<b>Input ranges (rated values), currents</b>	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	50 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation</b>	
Measurement principle	Actual value encryption
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	14 bit; Unipolar: 14 bit; bipolar: 13 bit + sign
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	52 µs per channel
• Interference voltage suppression for interference frequency f1 in Hz	none / 400 / 60 / 50 Hz
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
<b>Errors/accuracies</b>	
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to input area, (+/-)	0.4 %
• Current, relative to input area, (+/-)	0.3 %

<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input area, (+/-)	0.25 %
• Current, relative to input area, (+/-)	0.2 %
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes; Parameterizable, channels 0 and 2
<b>Diagnostic messages</b>	
• Diagnostic information readable	Yes
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
<b>Potential separation</b>	
Potential separation analog inputs	
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Connection method</b>	
required front connector	20-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	117 mm
<b>Weights</b>	
Weight, approx.	230 g

**last modified:** 09.04.2016