

SIMATIC S7-300, CP 340 COMMUNICATION PROCESSOR WITH
RS422/485 INTERFACE INCL. CONFIG. PACKAGE ON CD



Figure similar

General information

Product type designation	CP 340
--------------------------	--------

Supply voltage

Rated value (DC)	
• 24 V DC	No; Power supply via backplane bus 5V

Input current

from backplane bus 5 V DC, max.	165 mA
---------------------------------	--------

Power loss

Power loss, typ.	0.6 W
Power loss, max.	0.85 W

Interfaces

Number of interfaces	1; Isolated
Interface (physical) RS 422/485 (X.27)	Yes
Transmission rate, min.	2.4 kbit/s
Transmission rate, max.	19.2 kbit/s

Point-to-point

• Cable length, max.	1 200 m
• supported printers	HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
• Connector type	15-pin sub D socket
Integrated protocol driver	
— 3964 (R)	Yes
— ASCII	Yes
— RK512	No
— customer-specific drivers reloadable	No
Telegram length, max.	
— 3964 (R)	1 024 byte
— ASCII	1 024 byte
Transmission rate, RS 422/485	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	9.6 kbit/s
— with printer driver, max.	9.6 kbit/s
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Software	
Block	
• FB length in RAM, max.	2 700 byte; Data communication, sending and receiving
Connection method	
Power supply	Over backplane bus
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight	300 g
last modified:	11/21/2017